

**E14** 1055.06

**HIGHWAY RANGE**

EN ISO 20345:2011 CE  
S3 HRO SRC

**SIZES** EU 35-48  
UK 2<sup>1/2</sup> - 13  
MP 217 - 315



BREATHABLE LINING

BREATHABLE TEXTILE

DIRECTLY INJECTED PU + RUBBER

NUBUCK LEATHER  
HONEY



30% RECYCLED  
15% CORK



### CHARACTERISTICS

<b>SOLE</b> .....	DIRECTLY INJECT PU + RUBBER (w/ 30% recycled + 15% cork).....
<b>PROTECTIVE TOE CAP</b> .....	COMPOSITE (impact-resistant up to 200J).....
<b>PROTECTIVE MIDSOLE</b> .....	KEVLAR (perforation-resistant up to 1100 N).....
<b>UPPER MATERIAL</b> .....	TEXTILE - NAVY BLUE + NUBUCK - HONEY.....
<b>LINNING MATERIAL</b> .....	BREATHABLE TEXTILE - NAVY BLUE.....
<b>INSOLE</b> .....	LAVORO ESD TITAN.....
<b>WIDTH</b> .....	11.....



ESD  
(Electrostatic Discharge)



CLIMA CORK  
SYSTEM



RESISTANT  
UP TO 300°C



METAL FREE



ANTI-SLIP  
SOLE



LIGHTWEIGHT